

Date: Wednesday, 25/03/2009 2:02:20 PM  
 User: Chantal Lavoie

## Process Sheet

|                                    |                                     |                           |              |
|------------------------------------|-------------------------------------|---------------------------|--------------|
| <b>Customer</b> :                  | CU-DAR001 Dart Helicopters Services | <b>Drawing Name</b> :     | LABEL        |
| <b>Job Number</b> :                | 46707                               |                           |              |
| <b>Estimate Number</b> :           | 10064                               |                           |              |
| <b>P.O. Number</b> :               |                                     | <b>Part Number</b> :      | D2851170     |
| <b>This Issue</b> :                | 25/03/2009                          | <b>S.O. No.</b> :         |              |
| <b>Prsht Rev.</b> :                | NC                                  | <b>Drawing Number</b> :   | D2851 REV A1 |
| <b>First Issue</b> :               | 1/1                                 | <b>Project Number</b> :   | N/A          |
| <b>Previous Run</b> :              |                                     | <b>Drawing Revision</b> : | A1           |
| <b>Written By</b> :                |                                     | <b>Material</b> :         |              |
| <b>Checked &amp; Approved By</b> : | <u>C209/03/25</u>                   | <b>Due Date</b> :         | 01/04/2009   |
| <b>Comment</b> :                   | Est. A: 03.03.06 New Issue KJ/RF    | <b>Qty:</b>               | 10           |
|                                    |                                     | <b>Um:</b>                | Each         |

## Additional Product

Job Number:



|                |                              |                      |
|----------------|------------------------------|----------------------|
| <b>Seq. #:</b> | <b>Machine Or Operation:</b> | <b>Description :</b> |
|----------------|------------------------------|----------------------|

|     |    |            |
|-----|----|------------|
| 1.0 | PG | PURCHASING |
|-----|----|------------|



Comment: PURCHASING

Issue P/O: 8453

C209/03/25

(10)

Make D2851-170 read 170lb/77kg as per Dwg D2851 Material: Red letters (0.5" min height) with adhesive  
 back Manufacture from 3M 7mil masking film #8522CP or Avery IPM #2031  
 Material release note required

|     |           |       |
|-----|-----------|-------|
| 2.0 | D2851170P | Label |
|-----|-----------|-------|



Comment: Qty.: 1.0000 Each(s)/Unit Total: 10.0000 Each(s)  
 Label

|     |             |                       |
|-----|-------------|-----------------------|
| 3.0 | PACKAGING 1 | PACKAGING RESOURCE #1 |
|-----|-------------|-----------------------|



Comment: PACKAGING RESOURCE #1

Receive & Inspect For Transit Damage  
 Ensure material certification is attached

88 09/04/01

|     |     |                   |
|-----|-----|-------------------|
| 4.0 | QC6 | DIMENSIONAL CHECK |
|-----|-----|-------------------|



Comment: DIMENSIONAL CHECK  
 Ensure part as per Dwg D2851

09/04/02 (X10)

|     |             |                       |
|-----|-------------|-----------------------|
| 5.0 | PACKAGING 1 | PACKAGING RESOURCE #1 |
|-----|-------------|-----------------------|



Comment: PACKAGING RESOURCE #1

Identify and Stock  
 Location: 505

9/4/2

(10K)  
 SQ

| W/O: |      | WORK ORDER CHANGES |    |      |     |                                     |                          |
|------|------|--------------------|----|------|-----|-------------------------------------|--------------------------|
| DATE | STEP | PROCEDURE CHANGE   | By | Date | Qty | Approval<br>Chief Eng /<br>Prod Mgr | Approval<br>QC Inspector |
|      |      |                    |    |      |     |                                     |                          |
|      |      |                    |    |      |     |                                     |                          |

Part No: \_\_\_\_\_ PAR #: \_\_\_\_\_ Fault Category: \_\_\_\_\_ NCR: Yes No DQA: \_\_\_\_\_ Date: \_\_\_\_\_

Resolution: \_\_\_\_\_ Disposition: \_\_\_\_\_ QA: N/C Closed: \_\_\_\_\_ Date: \_\_\_\_\_

| NCR: |      | WORK ORDER NON-CONFORMANCE (NCR) |                                |                                 |                |                           |                       |                          |
|------|------|----------------------------------|--------------------------------|---------------------------------|----------------|---------------------------|-----------------------|--------------------------|
| DATE | STEP | Description of NC<br>Section A   | Corrective Action<br>Section B |                                 |                | Verification<br>Section C | Approval<br>Chief Eng | Approval<br>QC Inspector |
|      |      |                                  | Initial<br>Chief Eng           | Action Description<br>Chief Eng | Sign &<br>Date |                           |                       |                          |
|      |      |                                  |                                |                                 |                |                           |                       |                          |
|      |      |                                  |                                |                                 |                |                           |                       |                          |
|      |      |                                  |                                |                                 |                |                           |                       |                          |

**NOTE:** Date & initial all entries

Date: Wednesday, 25/03/2009 2:02:21 PM  
User: Chantal Lavoie

## Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: LABEL

Job Number: 46707

Part Number: D2851170

Job Number:



Seq. #:

Machine Or Operation:

Description :

6.0

QC21

FINAL INSPECTION/W/O RELEASE



09/04/06 JJA

Comment: FINAL INSPECTION/W/O RELEASE

Job Completion



mf 09-09-02

| W/O: |      | WORK ORDER CHANGES |    |      |     |                                     |                          |
|------|------|--------------------|----|------|-----|-------------------------------------|--------------------------|
| DATE | STEP | PROCEDURE CHANGE   | By | Date | Qty | Approval<br>Chief Eng /<br>Prod Mgr | Approval<br>QC Inspector |
|      |      |                    |    |      |     |                                     |                          |
|      |      |                    |    |      |     |                                     |                          |

Part No: \_\_\_\_\_ PAR #: \_\_\_\_\_ Fault Category: \_\_\_\_\_ NCR: Yes No DQA: \_\_\_\_\_ Date: \_\_\_\_\_

Resolution: \_\_\_\_\_ Disposition: \_\_\_\_\_ QA: N/C Closed: \_\_\_\_\_ Date: \_\_\_\_\_

| NCR: |      | WORK ORDER NON-CONFORMANCE (NCR) |                             |                                 |                |                           |                       |                          |
|------|------|----------------------------------|-----------------------------|---------------------------------|----------------|---------------------------|-----------------------|--------------------------|
| DATE | STEP | Description of NC<br>Section A   | Corrective Action Section B |                                 |                | Verification<br>Section C | Approval<br>Chief Eng | Approval<br>QC Inspector |
|      |      |                                  | Initial<br>Chief Eng        | Action Description<br>Chief Eng | Sign &<br>Date |                           |                       |                          |
|      |      |                                  |                             |                                 |                |                           |                       |                          |
|      |      |                                  |                             |                                 |                |                           |                       |                          |
|      |      |                                  |                             |                                 |                |                           |                       |                          |

**NOTE:** Date & initial all entries



|                      |                       |   |                        |
|----------------------|-----------------------|---|------------------------|
| DESIGN<br><i>KE</i>  | DRAWN BY<br><i>KE</i> | DART AEROSPACE LTD<br>HAWKESBURY, ONTARIO, CANADA |                        |
| CHECKED<br><i>JA</i> | APPROVED<br><i>JA</i> | DRAWING NO.<br>D2851                              | REV. A<br>SHEET 1 OF 1 |
| DATE<br>98.11.12     |                       | TITLE<br>LABEL                                    | SCALE<br>NTS           |
| A                    | 98.11.12              | NEW ISSUE   |                        |
| AI                   | <i>JA</i> 03.03.05    | ADDED D2851-170                                   |                        |

RELEASED  
98.11.18 KE


MAXIMUM DISTRIBUTED LOAD  
XXX lb/ YYY kg  
MAY BE SIGNIFICANTLY REDUCED BY LATERAL C OF G

D2851-XXX

XXX = MAX LOAD IN POUNDS

*C209/03/25*  
*W/O: 46707*

EXAMPLE

| <u>PART #</u>   | <u>LOAD</u>   |
|---|---------------|
| D2851-154   | 154 lb/70 kg  |
| D2851-160   | 160 lb/73 kg  |
| D2851-220   | 220 lb/100 kg |
|  D2851-170 | 170 lb/77 Kg  |

MATERIAL: RED LETTERS (0.5" MIN HEIGHT) WITH ADHESIVE BACK



## PRODUCT DATA BULLETIN

Product Data Bulletin: A5-O

**Avery Graphics™ A5 Opaque**  
5-year **INTERMEDIATE** calendered vinyl film  
Dated: 10/3/02

### Description:

Avery Graphics™ A5 Opaque intermediate films are flexible, high-gloss calendered vinyls designed for use on computer sign cutting equipment. This construction provides excellent cutting, weeding and transferring characteristics for signage applications.

Application information can be found in the Avery Graphics Application Guide.

For surface preparation, converting and printing, and application and removal instructions, please refer to the Avery Graphics Instructional Bulletin.

### Construction:

- Face Film: 3.2 mils opaque medium gloss intermediate calendered vinyl film
- Adhesive: 1.0 mil clear acrylic permanent solvent pressure-sensitive adhesive
- Liner: 78# bleached white kraft

### Physical Properties:

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification).

- Outdoor durability: 5 years when properly processed and applied (vertical exposure, unprinted film)\*\*
- Application surface contours: Flat and simple curves
- Minimum surface and air application temperature: +50° F (10° C)
- Service Temperature Range: -40° F to +180° F (-40° C to 82° C) (Reasonable range of temperatures which would be expected under normal environmental time and temperature conditions)
- Typical Chemical Resistance: Resistant to most mild acids, alkalis and salt solutions. See instructional bulletin for recommendations on cleaning.
- Shelf Life: One year when stored at the following temperatures and humidity conditions: 68°-77° F (20° - 25° C) and 50±5% R. H.
- Typical Adhesion Values: **180° Peels**

| Substrate       | 24 hrs     | 1 week     |
|-----------------|------------|------------|
| Stainless Steel | 4.4 lbs/in | 5.1 lbs/in |
| Glass           | 4.7 lbs/in | 5.3 lbs/in |

NOTE: Tested per ASTM D 1000. Always pre-test your specific substrate prior to actual application.

- Reflectivity: NA
- Typical Gloss\*: 70 at 60°



# Scotchcal™

## Opaque Imaging Media 8522

### Description

This media is specially formulated to dry quickly after printing. Production of outdoor weatherable and long-term indoor durable graphics is now easier than ever. Its changeable adhesive allows easy removal for up to one year.

### Advantages

- Optimized for use with selected Epson Stylus Pro printers and Epson Archival inks.
- Optimized for use with selected HP DesignJet Printers and HP DesignJet Ink System UV or HP83UV Color Ink System
- For making opaque, laminated graphics that are outdoor weatherable and long-term indoor durable
- Media:
  - For opaque (reflective) graphics
  - Changeable, easy to remove from warranted substrates up to 1 year later
  - Dries quickly after printing so the overlaminate can be applied almost immediately
  - Low slippage paper liner for superior tiling
- Overlaminates:
  - Provide additional UV (ultraviolet) and physical protection for making weatherable finished graphics
  - Available in luster and matte gloss
  - Adhesive allows for heat-assisted or cold-temperature lamination

### Applications and Uses

3M™ Scotchcal™ Changeable Opaque Imaging Media 8522 is intended only for ink jet printing and for use with the listed Compatible Products and Equipment and the following applications. Any other application is NOT warranted by 3M or covered by the worldwide 3M™ MCS™ Warranty unless 3M gives its prior written approval for the application.

- First surface images (the image is on top of the film) for opaque posters and signs, including:
  - Graphics for vans, personal vehicles, trucks and buses
  - Novelty posters
  - Retail and point-of-purchase displays
  - Information graphics such as maps and directories
  - Entertainment promotions in museums, zoos, parks, theatres, sports venues
  - Education and presentation graphics

### Product Bulletin 8522

Release F, Effective January 2003  
Black bar in margin indicates a change

- Legal and courtroom exhibits

- For flat or simple curved surfaces, with or without rivets, used in vertical ( $\pm 10^\circ$ ) applications

### Limitations of End Uses

The following uses and applications are specifically NOT warranted.

- Fleet applications in areas that use salt for winter road maintenance
- Application to non-warranted substrates, including wall-board
- Applications subjected to gasoline vapors or spills
- Application to corrugated or highly irregular surfaces or sharply raised areas
- Graphics applied to stainless steel, including stainless steel vehicles
- On flat surfaces with rivets, tenting of 4 to 10 mm around rivets may be expected; rivets may be cut around to eliminate tenting.

Note: Standard ink jet technology is water based. Water-based chemistry is susceptible to the extremes of heat and humidity. This is a factor in most product constructions on the market. Read the Fabrication, Shelf Life and Storage sections in this bulletin. Staying in the middle of these ranges always provides optimum performance.

### Compatible Products and Equipment

#### Thermal Ink Jet Printing Systems

- Epson Stylus Pro 9500, Stylus Pro 10000 printer
  - Epson Archival Inks
- Epson Stylus Pro 10600 printer
  - Epson Archival Inks
- HP DesignJet Printers 2000 and 3000 series
  - HP DesignJet Ink System UV (pigment-based ink)
- HP DesignJet Printers 5000 series
  - HP83UV Color Ink System

#### Overlaminates (required)

- 3M™ Luster Overlaminate 8519 (semi-gloss)
- 3M™ Matte Overlaminate 8520

Note: For the full product names of the 3M products listed on this page, please see page 1.

### Warranted Substrates

Media 8522 is warranted for use on the following rigid substrates.

Some substrates may "out-gas", resulting in tiny bubbles throughout the surface of the graphic. For maximum performance, be sure the substrate you select is properly cleaned and prepared as recommended by the manufacturer. See Instruction Bulletin 5.1 for additional information.

- Alodine (anodized aluminum)
- Automotive panels (automotive painted steel)
- Fruehauf (painted aluminum)
- FRP (fiberglass reinforced plywood)
- Glass
- Imron® (polyurethane-painted metal panel)
- Acrylic
- Sintra™ board

### Test and Approve Non-warranted Substrates Before Use

Media 8522 is not warranted for any substrate other than those listed above. If you want to use it for other substrates, 3M recommends that you test and approve the media for both adhesion and removal characteristics.

### Characteristics

| Characteristic                 | Description  |
|--------------------------------|--|
| Media                          | 7 mil, white, opaque graphic film  |
| Liner                          | Low-slippage, lay flat paper   |
| Adhesive                       | Changeable, pressure sensitive   |
| Thickness (media and adhesive) | 7.5 to 8 mil (nominal)   |
| Application substrates         | See Warranted Substrates, above  |
| Application surfaces           | Flat or simple curved surfaces, with or without rivets, used in vertical ( $\pm 10^\circ$ ) applications (no corrugations) |
| Application temperature range  | 28° to 110°F (-2° to 43°C)<br>(air and surface)  |
| Roll sizes                     | 36" x 45 feet (914 mm x 13.5 m)<br>54" x 45 feet (1372 mm x 13.5 m)  |

## How to Become a 3M Ink Jet Registered Fabricator

Only 3M Thermal Ink Jet Registered Fabricators are eligible to offer 3M MCS warranted graphics. In order to become certified, a fabricator must complete the requirements as specified in the 3M Ink Jet Graphics Registered Fabricator Reference Manual located on the 3M website at [www.scotchprint.com](http://www.scotchprint.com)

### Effective Performance Life

To obtain the warranty given below, the graphics must be made according to 3M's recommendations which are detailed in the Warranty and Limited Remedies on page 3. Also see the section, Removability.

### Warranted Durability

| Media 8522 with Overlaminates 8519 or 8520 | Epson Printers |         | HP Printers |         |
|--|----------------|---------|-------------|---------|
|  | Outdoor        | Indoor  | Outdoor     | Indoor  |
| Applied to Warranted Substrates            | 2 years        | 5 years | 3 years     | 5 years |

### Removability

Imaging media 8522 is removable from warranted substrates for 1 year without the aid of chemical strippers or accessories. Refer to Instruction Bulletin 4.23 for additional information.

### Fabrication


Graphics must be made according to 3M's recommendations which are detailed in the Warranty and Limited Remedies on page 3.

See Instruction Bulletin 4.23 for detailed fabrication, printing and mounting information.

### Graphic Construction Options

#### Opaque (Reflective) Graphics

Opaque graphics made with imaging media 8522 require an overlaminate and an opaque substrate.





Note: For the full product names of the 3M products listed on this page, please see page 1.

## Shelf Life and Storage

- 3M™ Scotchcal™ Changeable Opaque Imaging Media 8522 has a shelf life of one year.
- Storage conditions (new and partially used rolls). For optimum performance, use the middle of these ranges:
  - Original packaging, including plastic wrap
  - Relative humidity of 20% to 80%
  - Temperature of 33° to 104°F (0° to 40°C)
  - Away from direct sunlight
- Do not stack unprotected rolls or lay sharp or heavy objects on them.

## Health and Safety

### Caution

When handling any chemical products, read the manufacturers' container labels and the Material Safety Data Sheets (MSDS) for important health, safety and environmental information.

To obtain MSDS sheets for 3M products:

- By fax, call 1-800-364-0768 in the US and Canada or 1-650-556-8417 for all other locations.
- Electronically, visit us at <http://www.3M.com/msds>.
- By mail, or in case of an emergency, call 1-800-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturers' instructions for safe operation.

## Warranty and Limited Remedies

### 3M™ MCS™ Warranty for Graphics Produced on HP DesignJet Printers and Epson Stylus Pro Printers

The following is made in lieu of all other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose: We warrant graphics produced by a 3M Ink Jet Registered Fabricator made with imaging media 8522, printed on an approved HP thermal ink jet printer according to HP's recommendations or Epson Stylus Pro printer according to Epson's recommendations, overlaminated with 8519 or 8520, and applied to a Warranted Substrate according to 3M's recommendations. These

### 3M

#### Commercial Graphics Division

3M Center, Building 220-6W-06  
PO Box 33220  
St. Paul, MN 55133-3220 USA  
General Info: 1-800-374-6772  
Technical Info: 1-800-328-3908  
Fax: 1-651-736-4233

Fax-on-Demand: 1-800-364-0768 US/Canada or 1-651-732-6506 International  
Fax-on-Demand document: 4506  
[www.scotchprint.com](http://www.scotchprint.com)

#### 3M Canada

P.O. Box 5757  
London, Ontario  
Canada N6A 4T1  
1-800-265-1840  
Fax: 519-452-6245

graphics are covered against failure caused by ultraviolet light, temperature extremes, pollution, and other elements.

If a graphic fails to perform in accordance with 3M product specifications within this time frame, 3M will replace the materials at no charge. **These remedies are exclusive. In no case shall 3M be liable for any direct, indirect, or consequential damages, including any labor charges.**

## 3M Related Literature

Listed below is related 3M technical literature that may be of interest. You may view and print these Bulletins from our Web site at [www.scotchprint.com](http://www.scotchprint.com), or order them via our Fax-on-Demand (FOD) system. Call one of these phone numbers to order the desired bulletins, and specify the FOD document number provided in the chart.

United States or Canada: 1-800-364-0768  
International: 1-651-732-6506

| Subject   | Bulletin No. | FOD No. |
|---|--------------|---------|
| <b>Product Bulletins</b>  |              |         |
| 3M™ Scotchcal™ Overlamine 8519 and 8520   | 8519/8520    | 4524    |
| <b>Instruction Bulletins</b>  |              |         |
| Making thermal ink jet graphics   | 4.23         | 6523    |
| Application, substrate selection, preparation and substrate-specific application techniques | 5.1          | 7001    |
| <b>Warranties</b>   |              |         |
| Worldwide 3M™ MCS™ Warranty Packet (includes all Commercial Graphics MCS Warranties)        |              | 9503    |
| Worldwide 3M™ MCS™ Warranty Overview-Folder   |              | 9504    |

3M, Scotchcal and MCS are trademarks of 3M.  
Epson and Stylus Pro are trademarks of Epson.  
HP and DesignJet are tradenames of Hewlett Packard.  
Sintra is a trademark of Swiss Aluminum Ltd.  
Intron is a registered trademark of DuPont in the United States

### Bulletin Change Summary

The Epson Stylus Pro Printers 9500, 10000 10600, and Epson Archival Inks have been added to this bulletin. Additional changes resulting from this addition are marked with black bars in the margin.

#### 3M México, S.A. de C.V.

Av. Santa Fe No. 55  
Col. Santa Fe, Del. Álvaro Obregón  
México, D.F. 01210  
52-55-52-70-04-00  
Fax: 52-55-52-70-22-77

#### 3M Puerto Rico, Inc.

Puerto Rico Industrial Park  
P.O. Box 100  
Carolina, PR 00986-0100  
787-620-3000  
Fax: 787-750-3035

©3M 2003. All rights reserved.

Product Bulletin 8522 - 3

**210 MAIN W.,  
HAWKESBURY, ONT. K6A 2H6**  
**Tel.: 613 632-2001**  
**Fax: 613 632-9491**  
**[www.studiolettrage.com](http://www.studiolettrage.com)**

**INVOICE / FACTURE**

**VENDU À:**  
**SOLD TO:**

**LIVRÉ À:**  
**SHIPPED TO:**

No.: 11849  
DATE: 04/01/2009  
PAGE 1 of 1  
Re: Quote No. 6621

Dart Aerospace Ltd  
1270 Aberdeen  
Hawkesbury, Ontario K6A 1K7

Dart Aerospace Ltd  
Hawkesbury, Ontario

| ITEM<br>ARTICLE                         | QTY<br>QYÉ    | UNIT<br>UNITÉ | DESCRIPTION  | GST<br>TPS  | PST<br>TVP | UNIT PRICE<br>PRIX UNITÉ | AMOUNT<br>MONTA                      |
|---|---------------|---------------|--|-------------|------------|--------------------------|--------------------------------------|
|   | 20<br>10<br>2 |               | 41232200008001<br>D2851170P<br>set up<br><br>G - GST @ 5%; PST @ 8%<br>GST<br><br>PST Exempt: #6122-5207 | G<br>G<br>G |            | 1.25<br>5.00<br>50.00    | 25.00<br>50.00<br>100.00<br><br>8.71 |
| Studio de Lettrage GST: #869034678RP001 |               |               |  |             |            | <b>TOTAL</b>             | 183                                  |
| PO 8453                                 |               |               |  |             |            |                          |                                      |